

Datenblatt für Artikel: LID14850--

10108FA/B/C SCHWARZ LED 8W CW IP40 230V

Einbaudownlight, inklusive Treiber



Produktinfo

8W slim downlight LED, IP40, ideal for commercial applications such as offices, galleries and showrooms. Supplied with 300mA non-dimmable LED driver. Complies with standard EN60598-1 and any other specific standards.

Technische Daten

Lichtstrom (lm)	560
Lichtfarbe	kaltweiß
Farbtemperatur (K)	4000
Farbwiedergabeindex Ra	≥80
Lebensdauer	30.000h
Dimmbar	nein
Schutzklasse	II
Schutzart	IP40
Leuchtmittel inkl.	ja
Fassung	LED Platine
Ausstrahlwinkel (°)	120
Systemeffizienz (lm/W)	70
Leistungsfaktor	0,6

Technische Daten - Fortsetzung

Leistung (W)	8
Betriebsgerät	LED Treiber
Betriebsspannung AC (V)	220-240
Frequenz (Hz)	50/60
Montage	Deckeneinbau
Ausschnitt (mm)	Ø 108
Einbautiefe mm (mm)	50
Farbe	schwarz
Material	Acryl Kunststoff Alu Druckguss
Durchmesser (mm)	120
Optionales Zubehör	LID16949--
AUSSCHNITT mm	Ø 108

Maßbild: 10108FA/B/C SCHWARZ LED 8W CW IP40 230V



Artikeltabelle

BEZEICHNUNG	BEST.NR.
10108FA/B/C SCHWARZ LED 8W CW IP40 230V Einbaudownlight, inklusive Treiber	LID14850
Optionales Zubehör	
050180E FAST Kabel VERBINDER 32A 2x3-port 26 ACCES&GADGETS	LID16949